

ORDERING INFORMATION

■ AVAILABILITY/PART NUMBER

Spray-On Version:

16 oz/470mL: 350-M-00014 PT

1 gal/3.8L: 350-M-00014 GL

5 gal/19L: 350-M-00014 PL

55 gal/209L: 350-M-00014 DR

Spray-On & Polish Kit:

16 oz/470mL: 350-M-00014 KIT

Polishing Sponge: 350-X-00004 (2/pk)

Immersion Version:

16 oz/470mL: 350-M-00015 PT

1 gal/3.8L: 350-M-00015 GL

5 gal/19L: 350-M-00015 PL

55 gal/209L: 350-M-00015 DR

■ COVERAGE

186 ft² (17 m²) of 1 mil (25µm) rust removal per gallon.

Axxaclean™ 2048 is ready to use without dilution.

■ SHELF LIFE & HANDLING

Shelf life of 2 years if stored out of direct sunlight. Zerust® Axxaclean™ 2048 may freeze below -10°F (-23°C), but will remain fully functional when thawed to ambient temperature. Store above 32°F (0°F).

■ DISPOSAL

Dispose of chemistry in compliance with applicable local, national and international regulations.

ZERUST® AXXACLEAN™ 2048 PRODUCT INFORMATION

ZERUST RUST REMOVER COMPARISON

| Attributes | ICT®620-RR | Axxaclean 2048 | Axxaclean 3048 |
|---|--|---|---|
| Corrosion Removal Power | Light to medium rust even in cracks and crevices | Medium corrosion even in cracks and crevices | Heavy corrosion even in cracks and crevices |
| Speed | Slow | Moderate | Rapid |
| Metals Treated | Ferrous | Ferrous, brass, copper | Ferrous, brass, copper |
| Application Methods | Immersion | Immersion, dip, spray | Immersion, dip |
| pH Level | Neutral pH of about 7 | Mild acidic pH of about 2 | Stronger acidic pH between 0.5-1.5 |
| Temperature For Use | 70°F (21°C) or above | 70°F (21°C) or above | 40°F (4°C) or above |
| Compatibility (<24 hour soak) | Safe for metals*, paint, gaskets, rubber, plastics | Safe for metals*, paint, gaskets, rubber, plastics | May attack soft metals*, some paints and coatings |
| Post-Cleaning Action | Do not let product dry on surface. Water rinse, dry and wipe any carbon residue. | Do not let product dry on surface. Recommended DI or RO water rinse. Wipe off and dry well. | Do not let product dry on surface. Recommended DI or RO water rinse. Wipe off and dry well. |
| Corrosion Protection | Additional corrosion protection needed | Provides flash-corrosion protection in controlled environments | Provides flash-corrosion protection in controlled environments |
| Environmental Disposal | Non-hazardous. Pure product is neutral. Check local, national and international regulations. | Check for options for neutralizing. Check local, national and international regulations. | Do not dispose into waterways. Check local, national and international regulations. |
| Personal Protection | Optional gloves and eye protection | Gloves and eye protection | Ventilation, gloves, face shield and apron |

*Test before use on zinc and cadmium. Check with your Zerust technical representative for details.

OTHER PRODUCTS AVAILABLE

Axxaclean™ 3048 Heavy Rust Remover

Easy-to-use, fast acting and rust remover for extreme corrosion.

Axxanol™ Family of Corrosion Protective Coatings

Use Z-Maxx for long-term outdoor corrosion protection.

ICT®500 Series: Packaging Films

Our most widely used series of products. A variety of films offer short or long-term corrosion protection for parts and equipment during storage or shipment.

Warranty and Disclaimer Information:

We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied. See www.zerust.com/warranty.

©2012 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: NTI®, ZERUST®, The ZERUST People®, ActivPak®, Cor-Tab®, Flange Saver®, Plastabs®, ICT®, COR-SCI®, Z-CIS® and the Color "Yellow". EXCOR®, VALENO®, ABRIGO® and UNICO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

REV F



A product of:
Northern Technologies International Corporation
 4201 Woodland Road
 P.O. Box 69
 Circle Pines, MN 55014
 PH: +1 (763) 225-6600
 FAX: +1 (763) 225-6645
 EMAIL: sales@zerust.com
 WEB: www.zerust.com