



ZERUST®/EXCOR® ICT® Plastabs® are thin, light, rigid polyethylene diffusers that are made with ZERUST® Vapor Corrosion Inhibiting (VCI) technology. Their small, thin shape makes Plastabs® perfect for protecting critical surfaces within narrow or hard-to-reach areas of electronics or parts of equipment or as a supplement to other ZERUST® VCI packaging products for added protection. ZERUST® Plastabs® are easy to use, as they can be dispersed throughout bulk packages of metal parts and tightly seal the packaging or enclosure to trap the protective vapors inside. Additionally, the .75" x .75" size has an optional peel-adhesive backing that can be affixed to most surfaces.

Plastabs® diffuse invisible, odorless, and non-toxic ZERUST® VCI molecules that settle onto exposed metal surfaces inside the packaging or enclosure. Upon removal from the packaging or enclosure, the VCI will dissipate from the metal surfaces, allowing immediate painting, welding, or further processing. Plastabs® protects ferrous metals for up to 2 years<sup>†</sup> in a sealed enclosure. Additionally, they provide limited aluminum and yellow metal protection when used as instructed. However, do not place Plastabs® in direct contact with aluminum, copper, brass, or zinc, and test before use.

For over 50 years, ZERUST® VCI technology has proven its performance and safety with thousands of customers worldwide. It is used to protect valuable metal items for manufacturers in industries such as automotive, agricultural, aerospace, and mining. ZERUST®/EXCOR® offers on-site support and service in more than 70 countries via a network of 21 joint venture partnerships. Check with your ZERUST®/EXCOR® representative for a comprehensive corrosion management solution that is most effective for your metal assets.

## Typical Properties

Appearance Yellow thin, light, rigid polyethylene diffusers.

Substrates Ferrous protection. Limited aluminum and yellow metal protection when used as instructed. Do not place in direct contact with aluminum, copper, brass, or zinc, and test before use.

***This data sheet provides general guidelines for operation, application, and removal. Please contact your ZERUST®/EXCOR® account representative for more specific recommendations on your particular operation and conditions.***

## Operating Summary

- Remove the product from the packaging.
- Take note of the installation date. Plastabs® are rated to provide up to 2 years<sup>†</sup> of protection (See Protection Info on page 2 for specific protection capabilities).
- Place the Plastabs® in the most ideal location possible following the principles below:
  - Center: The ideal location to obtain maximum coverage of protection from the Plastab®. This position may not be possible if the center is occupied.
  - Corner: In deeper enclosures, two Plastabs® may be required on diagonally opposed corners to fully protect the entire space.
  - Sides: This is practical for most applications and provides the optimum side-mounted protection.
  - Dual Placement: For longer boxes or divided spaces, place Plastabs® in opposite corners for complete coverage.
- Ensure that the airflow to the enclosure is restricted. It is essential to restrict airflow to the container, as airflow removes the protective vapor barrier from the space faster than it can be released from the Plastabs®.
  - When applying Plastabs® within enclosures where the air is replaced regularly, such as air-cooling systems for computer equipment, it is recommended to place the Plastabs® close to the source of airflow. For added corrosion protection, consider placing additional Plastabs® near the sensitive metal surface to be protected.
- Upon removal of the Plastabs® or opening the enclosure, the ZERUST® protective molecules will dissipate from the metal surface in a few hours. Corrosion protection of the metal surface will also cease by this time.

Scan QR for more



product information  
and photos

## Availability

ZERUST®/EXCOR® Plastabs® are in stock for immediate delivery and sold in cases. Contact your ZERUST®/EXCOR® representative for ordering information.

Part Number	Size	Adhesive Backing	Debossed	Quantity
425-M-00001	1" x 1"	No	No	1,000/Case
425-M-00002	0.75" x 0.75"	No	No	1,000/Case
425-M-00003	0.50" x 0.50"	No	No	1,000/Case
425-M-00004	0.75" x 0.75"	Yes	No	1,000/Case
425-M-00010	1" x 3"	No	Yes	1,000/Case

## Protection Info‡

Size*	Protection Volume (Up to)‡	Protection Radius (Up to)‡	Protection Duration (Up to)‡
0.5" x 0.5"	0.1 ft <sup>3</sup> (0.003 m <sup>3</sup> )‡	0.3 ft (0.09 m)‡	2 years‡
0.75" x 0.75"	0.2 ft <sup>3</sup> (0.006 m <sup>3</sup> )‡	0.4 ft (0.1 m)‡	2 years‡
1" x 1"	0.4 ft <sup>3</sup> (0.01 m <sup>3</sup> )‡	0.5 ft (0.15 m)‡	2 years‡
1" x 3"	1.0 ft <sup>3</sup> (0.28 m <sup>3</sup> )‡	0.6 ft (0.2 m)‡	2 years‡

\*Dimensions are +/- 10%

## Storage

- Store in a cool, dry place and away from sunlight in the original packaging.
- Optimal storage temperature is < 85°F (29°C) and 50% RH for up to 2 years from the date of shipment.
- Reseal packaging after use. Products exposed to the environment over prolonged periods of time may become less effective.

## Disposal

- The contents of Plastabs® do not meet the criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P, or U lists; not ignitable, not corrosive, not reactive, and not toxic).
- Plastabs® may be disposed of in the general solid waste trash.
- Since regulations vary by location, ZERUST® advises our customers to review local regulations to ensure proper disposal.

## Precautions

- Do not install the Plastabs® where it will be submerged in water.
- Avoid placing metal surfaces in direct contact with wood or cardboard (sources of moisture and acid).
- Keep away from children. Safe for people. This product does not pose a health hazard to users due to its classification as an article according to UN GHS, US OSHA HazCom, and CA WHMIS regulations.
- Refer to the Safety Data Sheet (SDS) for more safety information.

### ‡ DECLARATION

Corrosion protection claims are based on Northern Technologies International Corporation (NTIC) internal laboratory testing performed under controlled parameters on contaminate-free substrates. Real-world application corrosion protection duration on different substrates will vary and depends on factors such as, but not limited to, the application or use, environmental / storage conditions, surface cleanliness, type of substrates, and coating thickness (where applicable). The use of the term "Up to" in reference to time is defined as any time duration from zero up to a specified time frame, but in no event beyond the specified time frame. The use of the term "for years" is based on NTIC's experience with its products but is in no way guaranteed. The use of the term "Up to" in reference to volume is defined as any volume from zero up to a specified volume but in no event beyond the specified volume of protection. It is the customer's / user's obligation to evaluate product performance, corrosion protection duration, safety, and suitability for intended use within the scope advised in the data sheet and to comply with all applicable laws and regulations. **LIMITED WARRANTY/DISCLAIMER** Warranty is limited to the replacement of a product that fails to meet specifications. For full warranty and disclaimer information, visit [www.zerust.com/warranty](http://www.zerust.com/warranty).

©2013-2025 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICB®, ICT®, Natur-VC1®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, 洁乐特, Z-PAK® and the Color "Yellow". ABRIGO®, UNICO®, ICB®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.