

ZERUST - EXCOR VCI

✓ Zerust[®] ICT[®]510-C VCI Ferrous Film

Zerust[®]/Excor[®] ICT510-C VCI Film provides cost-effective and versatile protection against corrosion damage for ferrous metals in shipping and storage. It protects steel, iron, cast iron and its alloys. It is available in various sized rolls, sheets, tubing and bags.

Zerust VCI packaging film diffuses proprietary Zerust VCIs (Vapor Corrosion Inhibitors) to protect metals from rust. Use Zerust ICT510-C VCI Film to protect metal components and assemblies, machined and cast parts, and more for years. For additional protection and use in challenging environments, packaging can be used with Zerust corrosion inhibitor liquid RPs and VCI diffuser products. Check with your Zerust/Excor representative for a comprehensive corrosion management solution most effective for your metal assets.

Zerust is the inventor of poly VCI technology and Zerust VCI film has proven its performance and safety* with thousands of customers worldwide for over 35 years. It is used to protect valuable metal items for manufacturers in industries such as automotive, agricultural, aerospace and mining. Zerust/Excor offers onsite support and service in more than 70 countries via a network of 29 joint venture partnerships.

Application Example

A ferrous Zerust VCI Film gusseted bag lines a dunnage system to protect precision steel parts from corrosion in shipping.



▶ Benefits

Effective corrosion protection and packaging combined in one step

Metals are ready for use and assembly directly out of the packaging

Available in many different shapes and sizes

Provides safe* and effective Zerust VCI protection.

Recyclable

Application Type

Storage
Shipping
Work in progress

*Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.

Product Information



Description	Zerust®/Excor® ICT®510-C VCI Film is a polyethylene product impregnated with volatile corrosion inhibitors.
Appearance	Typical colors are clear, yellow or green. Additional colors available upon request. Subject to order minimums.
Protected Metal Types	Protects ferrous metals such as steel, iron and its alloys.
Protection Life	Protects clean metals for years when used correctly and utilized within three years from receipt. Not intended for outdoor use.
Storage	Store in original packaging away from direct sunlight in conditions below 85°F (30°C) and 50% RH until ready for use.

Property	Direction (Machine or Transverse)	Zerust ICT510-C Film*	ASTM Test Method
Film Thickness	-	4 mil (102 µm)	D-6988
Dart Impact Resistance	-	300 g	D-1709
Tear Strength	MD	0.60 lb-f (2.7 N)	D-1938
	TD	0.65 lb-f (2.9 N)	
Tensile Strength at Yield	MD	1905 psi (13.1 MPa)	D-882
	TD	1538 psi (10.6 MPa)	
Tensile Strength at Break	MD	3045 psi (21.0 MPa)	D-882
	TD	2917 psi (20.1 MPa)	
Elongation at Break	MD	560%	D-882
	TD	610%	
Breaking Factor	MD	11.0 lb-f/in (1926 N/m)	D-882
	TD	11.5 lb-f/in (2014 N/m)	
Water Vapor Transmission Rate @78°F (26°C), 90% RH	-	0.06 g/(100 in²/day)	F-1249
Vapor Inhibiting Ability (VIA)	-	Pass	NACE TM0208-2013

* Typical values, not meant to be a specification.

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. All statement, technical information and recommendations contained herein are based on testing and experiences NTIC believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2017 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor-Tab®, EXCOR®, Flange Saver®, ICT®, NIT®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, The ZERUST People®, and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Contact Us



A product of:
Northern Technologies
International Corp
4201 Woodland Road
Circle Pines, MN 55014
USA

Availability

Zerust/Excor ICT510-C VCI Ferrous Film is available in many stock and custom options such as UV and Anti Static Additives. Contact a Zerust account manager for pricing and availability.

Size Range (width):

Bags & Tubing:
2" - 125" (flat)
2" - 150" (gusset)
Sheeting: 2" - 26'

Recyclable

Dispose of in accordance with local, national and international regulations. Check on options for recycling and incineration.

Safety

- Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.
- Zerust VCI chemistry is safe for sensitive electronics. No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.

Phone. +1 763.225.6600
Fax. +1 763.225.6645
sales@zerust.com
www.zerust.com

