

Zerust[®] Axxanol[™] Z-Maxx Series

For a hard-working corrosion preventative grease—use Zerust[®] Axxanol[™] Z-Maxx or Z-Maxx LV. Z-Maxx greases provide extreme corrosion prevention for ferrous and non-ferrous metals for up to one year outdoors and two years under shelter.

Zerust/Excor[®] Axxanol Z-Maxx is ideal for protecting bare-metal parts and components of machinery and equipment in extreme weather and salt-air conditions. Z-Maxx can be used for protecting parts during operation or long-term storage. Z-Maxx outperforms most petroleum-based corrosion preventive coatings and is easier to apply and remove—saving labor and maintenance costs.

Z-Maxx is a thick NLGI 2 grease and is also offered as Z-Maxx LV, a lower viscosity NLGI 0 grease. Both types offer exceptional corrosion protection while the original Z-Maxx is also a multipurpose EP lubrication grease for high-temperature range applications. Z-Maxx LV is designed for spreadability and has light lubrication properties.

Z-Maxx has very little odor and when applied in a thin uniform layer it creates a translucent film that allows visibility of the metal surface. It is hydrophobic and is compatible with synthetic rubber and plastics. For a sprayable Z-Maxx grease version, see information on Zerust Axxanol Spray-G.

Application Example

Z-Maxx was applied to critical metal parts on wind generators and solar panels in preparation for shipping. Upon arrival, customers installed them without need for removing the protective coating.



Benefits

- Superior corrosion protection
- Long-term protection even outdoors
- Multipurpose lubricant grease
- Available in different formats for ease of application
- Safe* and easy to apply and remove
- Tenacious and resistant to water

Application Type

- Storage
- Shipping
- During Operation
- May be used with Zerust packaging

*Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).



Technical Data

Product Series Information	Corrosion inhibitor lubricant greases.	
Application	Z-Maxx Original Apply via brush or cloth	Z-Maxx LV Apply via brush or cloth
Application Temp	-13 to 176°F (-25 to 80°C)	-13 to 176°F (-25 to 80°C)
Coverage	290 ft ² (27 m ²) / gal	290 ft ² (27 m ²) / gal
Wet Film Thickness*	5 mil (127 µm)	5 mil (127 µm)
Grease Grade	NLGI 2	NLGI 0
Removability	Alkaline cleaner	Alkaline cleaner
VOC Content	Not Applicable	Not Applicable
Flash Point	475°F (246°C)	390°F (200°C)

Protection Specs

Metal types	Multimetal protection	Multimetal protection
Copper Compatibility	Pass	Pass
Salt Fog (ASTM B-117)	>500 Hrs @ 2 mil	>500 Hrs @ 2 mil
Indoors	Up to 2 years	Up to 2 years
Outdoors	Up to 1 year	Up to 1 year
In VCI Packaging/ Hermetically Sealed	Up to 5 years	Up to 5 years

Storage Temp	Store in a cool (50 to 90°F / 10 to 32°C), dry place and away from sunlight in original packaging for up to 2 years from the date of shipment.
Shelf Life	

*A change in thickness of coating will result in a change in coverage. Typical application thickness ranges from 5 to 20 mil. Theoretical coverage is 1450 ft² (135 m²) / gallon at 1 mil (24 µm) wet film thickness.

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2019 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastab®, Z-CIS®, Zerion®, ZERUST®, 洁乐特 and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Contact Us

ZERUST® EXCOR®

A product of:
Northern Technologies
International Corp.
4201 Woodland Road
Circle Pines, MN 55014
USA

Availability

Zerust®/Excor® Axxanol™ Z-Maxx is a ready-to-use grease product sold by volume. For sprayable version see infosheet for Axxanol Spray-G.

Part Number	Qty
Axxanol Z-Maxx	
360-M-00001PL	5 Gal*
360-M-00001DR	55 Gal*
Axxanol Z-Maxx LV	
360-M-00002PL	5 Gal*
360-M-00002DR	55 Gal*
Axxanol Spray-G (Z-Maxx Spray)	
350-M-00023AC	12 oz
350-M-00023PL	5 Gal*
350-M-00023DR	55 Gal*

*5 Gallon approx. 35 lbs, 55 Gallon approx. 400 lbs

Safety

- Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).
- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

Phone. +1 763.225.6600
Fax. +1 763.225.6645
sales@zerust.com
www.zerust.com

