

Zerust® Axxanol™ Z-Maxx Series

For a hard-working corrosion preventative grease—use Zerust® Axxanol™ Z-Maxx or Z-Maxx LV. Z-Maxx greases provide extreme corrosion prevention for ferrous and non-ferrous metals for up to one year outdoors and two years under shelter.

Zerust®/Excor® Axxanol™ Z-Maxx is ideal for protecting bare-metal parts and components of machinery and equipment in extreme weather and salt-air conditions. Z-Maxx can be used for protecting parts during operation or long-term storage. Z-Maxx outperforms most petroleum-based corrosion preventive coatings and is easier to apply and remove—saving labor and maintenance costs.

Z-Maxx is a thick NLGI 2 grease and is also offered as Z-Maxx LV, a lower viscosity NLGI 0 grease. Both types offer exceptional corrosion protection while the original Z-Maxx is also a multipurpose EP lubrication grease for high-temperature range applications. Z-Maxx LV is designed for spreadability and has light lubrication properties.

Z-Maxx has very little odor and when applied in a thin uniform layer it creates a translucent film that allows visibility of the metal surface. It is hydrophobic and is compatible with synthetic rubber and plastics. For a sprayable Z-Maxx grease version, see information on Zerust® Axxanol™ Spray-G.

Application Example

Z-Maxx was applied to critical metal parts on wind generators and solar panels in preparation for shipping. Upon arrival, customers installed them without need for removing the protective coating.



Benefits

Superior corrosion protection

Long-term protection even outdoors

Multipurpose lubricant grease

Available in different formats for ease of application

Safe* and easy to apply and remove

Tenacious and resistant to water

Application Type

Storage
Shipping
During Operation
May be used with Zerust® packaging

*Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).



Technical Data

Product Series Information	Corrosion inhibitor lubricant greases.	
Application	Z-Maxx Original Apply via brush or cloth	Z-Maxx LV Apply via brush or cloth
Application Temp	-13 to 176°F (-25 to 80°C)	-13 to 176°F (-25 to 80°C)
Coverage	290 ft ² (27 m ²) / gal	290 ft ² (27 m ²) / gal
Wet Film Thickness *	5 mil (127 µm)	5 mil (127 µm)
Grease Grade	NLGI 2	NLGI 0
Removability	Alkaline cleaner	Alkaline cleaner
VOC Content	Not Applicable	Not Applicable
Flash Point	475°F (246°C)	390°F (200°C)

Protection Specs

Metal types	Multimetal protection	Multimetal protection
Copper Compatibility	Pass	Pass
Salt Fog (ASTM B-117)	>500 Hrs @ 2 mil	>500 Hrs @ 2 mil
Indoors	Up to 2 years	Up to 2 years
Outdoors	Up to 1 year	Up to 1 year
In VCI Packaging/ Hermetically Sealed	Up to 5 years	Up to 5 years

Storage Temp	Store in a cool (50 to 90°F / 10 to 32°C), dry place and away from sunlight in original packaging for up to 2 years from the date of shipment.
Shelf Life	

*A change in thickness of coating will result in a change in coverage. Typical application thickness ranges from 5 to 20 mil. Theoretical coverage is 1450 ft² (135 m²) / gallon at 1 mil (24 µm) wet film thickness.

DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on validations and tests conducted by Northern Technologies International Corporation/Zerust® or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Northern Technologies International Corporation/Zerust® or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the film sold.

Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall Northern Technologies International Corporation/Zerust® be liable for incidental or consequential damages.

For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2020 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST® 浩乐特 and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Availability

Zerust®/Excor® Axxanol™ Z-Maxx is a ready-to-use grease product sold by volume. For sprayable version see infosheet for Axxanol™ Spray-G.

Part Number	Qty
Axxanol™ Z-Maxx	
360-M-00001PL	5 Gal*
360-M-00001DR	55 Gal*
Axxanol™ Z-Maxx LV	
360-M-00002PL	5 Gal*
360-M-00002DR	55 Gal*
Axxanol™ Spray-G (Z-Maxx Spray)	
350-M-00023AC	12 oz
350-M-00023PL	5 Gal*
350-M-00023DR	55 Gal*

*5 Gallon approx. 35 lbs, 55 Gallon approx. 400 lbs

Safety

- Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).
- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

A product of:
Northern Technologies
International Corp
4201 Woodland Road
Circle Pines, MN 55014
USA

Phone. +1 763.225.6600
Fax. +1 763.225.6645
sales@zerust.com
www.zerust.com

